

BALAD

3602 - SET OF 3 LAMPS H.12 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE

2 IREP

IRCY



Polyethylene diffuser

Aluminium frame

ABS base

Technology: integrated LED - Luminous flux: 20 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%) 10 h

Battery use cycle: 500 cycles


Recharge time: 4h - Type of recharge: USB, cable (supplied) 1,5m

Bypass to prevent battery damage during wired use

0.25 A - 5 V - 0.3 W | IP44 | IK 10 | CE | FCC | UKCA

Powered by Smart & Green

360282	● Cactus	360273	● Honey
360247	● Anthracite	3602B9	● Black Cherry
360221	● Acapulco Blue	360220	● Red Ochre
360214	● Nutmeg	3602A5	● Clay Grey



x3

0,13 kg



3612 - LAMP H.25 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE

2 IREP

IRCY



Polyethylene diffuser

Aluminium frame

ABS base

Technology: integrated LED - Luminous flux: 40 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 neutral white (4000°K) 50% brightness

Position 4 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%) 7 h

Battery use cycle: 300 cycles


Recharge time: 5h - Type of recharge: USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

0.5 A - 5 V - 0.5 W | IP44 | IK 10 | CE | FCC | UKCA

Powered by Smart & Green

361282	● Cactus	3612C6	● Honey
361247	● Anthracite	3612B9	● Black Cherry
361221	● Acapulco Blue	3612A5	● Clay Grey



0,53 kg



BALAD

3622 - LAMP H.38 CM
DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE

2 IREP

IRCY



Polyethylene diffuser
Aluminium frame
ABS base
Technology: integrated LED - Luminous flux: 150 lm
Switch type: push button
Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)
Lighting mood:
Position 1 cool white (6000°K) 100% brightness
Position 2 cool white (6000°K) 50% brightness
Position 3 neutral white (4000°K) 100% brightness
Position 4 neutral white (4000°K) 50% brightness
Position 5 candle-style warm white (2300°K) flickering
Type of power supply: battery - Min. Battery life (100%) 9 h
Battery use cycle: 300 cycles
Recharge time: 7h - Type of recharge: USB, cable (supplied) 2m
Bypass to prevent battery damage during wired use
2 A - 5 V - 2.5 W | IP44 | IK 10 | CE | FCC | UKCA
Energy rating: E
Powered by Smart & Green



- | | | | |
|--------|-----------------|--------|----------------|
| 362282 | ● Cactus | 362220 | ● Red Ochre |
| 362247 | ● Anthracite | 3622B9 | ● Black Cherry |
| 362221 | ● Acapulco Blue | 3622A5 | ● Clay Grey |
| 362273 | ● Honey | | |



BALAD

3632 - SPIKE STAND

DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE

2
IREP

IRCY

6⁷
IPAC



Steel wire frame
Steel clip on the ball joint system, with protective rubber pads
Compatible with:
LAMP H.25 CM - BALAD
LAMP H.38 CM - BALAD

363282 ● Cactus
363247 ● Anthracite
363221 ● Acapulco Blue

3632C6 ● Honey
3632B9 ● Black Cherry
3632A5 ● Clay Grey

21
159
2,80 kg



3631 - UPRIGHT STAND

DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE

2
IREP

IRCY

7
IPAC



Steel wire frame
Steel ballast
Steel clip with protective rubber pads
Compatible with:
LAMP H.25 CM - BALAD
LAMP H.38 CM - BALAD

363182 ● Cactus
363147 ● Anthracite
363121 ● Acapulco Blue

3631C6 ● Honey
3631B9 ● Black Cherry
3631A5 ● Clay Grey

20
157
Ø35
6,50 kg



3630 - OFFSET STAND


DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE

2
IREP

IRCY

7
IPAC



Steel wire frame
Steel ballast
Steel clip with protective rubber pads
Compatible with:
LAMP H.38 CM - BALAD
LAMP H.25 CM - BALAD

363082 ● Cactus
363047 ● Anthracite
363021 ● Acapulco Blue
363020 ● Red Ochre


3630C6 ● Honey
3630B9 ● Black Cherry
3630A5 ● Clay Grey

128
190
12 kg



Recommendations for appropriate installations:

**Choose
Balad H.25 cm
with:**



**Choose
Balad H.38 cm
with:**



BALAD

CONTRACT EXCLUSIVITY

3600 - SET OF 6 LAMPS H. 12 CM (CONTRACT)

DESIGN BY TRISTAN LOHNER



Polyethylene diffuser

Aluminium frame

ABS base

Technology: integrated LED - Luminous flux: 20 lm

Switch type: push button

Lighting mood:

Position 1 warm white (2700°K) 100% brightness

Position 2 candle-style warm white (2700°K) flickering

Position 3 neutral white (4000°K) 100% brightness

Position 4 candle-style neutral white (4000°K) flickering

Position 5 cool white (6000°K) 100% brightness

Position 6 candle-style cool white (6000°K) flickering

Type of power supply: battery - Min. Battery life (100%): 10 h

Battery use cycle: 500 cycles

Recharge time: 4h - Type of recharge: USB charging on steel charging pack

(not supplied) - White light indicator (1 Lm) when charging

Remote control (max. 5 metres, 20° angle) with infrared remote (2 supplied)

Power OFF mode: long press (5 seconds) (flash = infrared disabled) on the touch button under the lamp or on the charging pack

0.25 A - 5 V - 0.3 W - IP44 | IK 10 | CE | FCC

Powered by Smart & Green


Compatible with :

CHARGING PACK – SET OF 6 LAMPS H. 12 CM (CONTRACT) - BALAD

360026 ● Storm Grey

360029 ● Verbena

360014 ● Nutmeg



0,13 kg



3643 - CHARGING PACK – SET OF 6 LAMPS H. 12 CM (CONTRACT)

DESIGN BY TRISTAN LOHNER



Steel frame

Steel shell

Type of power supply : USB - Cable (supplied) 2 m

6-point charging base for set of 6 Balad H. 12 lamps (Contract)

Lamp affixed to the base with magnet system

2 T-shaped openings on the back to affix flush to the wall (horizontal or vertical)

Compatible with :

SET OF 6 LAMPS H. 12 CM (CONTRACT) - BALAD

364326 ● Storm Grey



1,10 kg



BALAD

365100 - SET OF 3 LAMPS BAMBOO H.12 CM


DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE

2 IREP

IRCY

INDOOR



Polyethylene diffuser

Bamboo frame

ABS base

Technology: integrated LED - Luminous flux: 20 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%) 10 h


Battery use cycle: 500 cycles

Recharge time: 4h - Type of recharge: USB, cable (supplied) 1,5m

Bypass to prevent battery damage during wired use

0.25 A - 5 V - 0.3 W - IP44 | IK 10 | CE | FCC | UKCA

Powered by Smart & Green



0,13 kg



365200 - LAMP BAMBOO H.25 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE

2 IREP

IRCY

INDOOR



Polyethylene diffuser

Bamboo frame

ABS base

Technology: integrated LED - Luminous flux: 40 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 neutral white (4000°K) 50% brightness

Position 4 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%) 7 h


Battery use cycle: 300 cycles

Recharge time: 5h - Type of recharge: USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

0.5 A - 5 V - 0.5 W - IP44 | IK 10 | CE | FCC | UKCA

Powered by Smart & Green



0,47 kg



BALAD

365300 - LAMP BAMBOO H.38 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE

2 IREP

IRCY

INDOOR



Polyethylene diffuser

Bamboo frame

ABS base

Technology: integrated LED - Luminous flux: 150 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 cool white (6000°K) 50% brightness

Position 3 neutral white (4000°K) 100% brightness

Position 4 neutral white (4000°K) 50% brightness

Position 5 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%) 9 h

Battery use cycle: 300 cycles


Recharge time: 7h - Type of recharge: USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

2 A - 5 V - 2.5 W - IP44 | IK 10 | CE | FCC | UKCA

Energy rating: E

Powered by Smart & Green



CM



BALAD BAMBOO

